



NIYATECH ENGINEERS

Thermal inkjet NT 2540

**Zero Breakdown
Ensure maximum up time
No hidden cost
Only ink cartridge is consumable
and maintenance part.**

Handheld Inkjet Printer

Nozzle	TU Thermal Foaming
Operating System	Linux
CPU	Quad Core 1.4Hz
Language	English, Chinese, Turkish, Arabic, Korean, Italian...
Shape Features	ABS
Dimension	130*128*242mm
Net Weight	1.0kg
Printing Height	25.4mm
Printing Distance	2.5 mm
Print content	Text, time, Batch number, serial number, logo, QR
Definition	Maximum 600 Dpi
Storage	More than 1000 Messages
Printing Length	2000 Characters for each message, no limitation
Printing speed	70m/min
Ink Colour	Black, Red, Blue, Green
External Interface	USB, Photocell
Voltage	DC 16.8 Lithium Battery (2600mAH*4)
Power Consumption	Lower than 5w
Working environment	Temperature : 0 – 38 Degree, Humidity: 10% - 80%
Printing Material	Board, Carton, Stone, Pipe, Cable, Metal, Plastic product, electronic, Fibre board, Light steel keel.



NIYATECH ENGINEERS

NIYATECH ENGINEERS

A-27, SECOND FLOOR GOVINDPURAM GHAZIABAD U.P. 201013

MO. +91- 8375877122 EMAIL. INFO@NIYATECHENGINEERS.COM GST- 09ASJPG3404D1Z5