



Thermal inkjet **NT 650**



T2.5 Inkjet technology

Zero Breakdown Ensure maximum up time No hidden cost Only ink cartridge is consumable and maintenance part.

PRODUCTS

Print Features

Printing direction:	Adjusted within 360 degree, meet all kinds of production needs.
Character type:	high-de nition printing character, dot matrix font, Simpli ed, Traditional Chinese and English
Function:	Handheld print and On line printing (Need Sensor extra)
Printing pictures:	Pictures(BMP Monochrome single bitmap format) can be uploaded through USB disk
Printing accuracy:	300DPI 400DPI 600DPI
Printing height:	2mm-12.7mm
Print code:	bar code, QR Code
Printing distance:	1-10mm Mechanical Adjustment (the best distance between the nozzle and printed object is 2-5mm)
Print serial number	
Automatic print:	.date, time, batch number shift and serial number, etc external USB save the information
Storage:	
	transfer in a free way
Messagelength	2000 characters for each message, not more than 1200mm length
Printing speed:	60m/min
Ink type:	Quick-dry environmental ink, water- based ink and oily ink
Ink color:	black, white, red, blue, yellow, green, invisible



Physical Features

· · · · · · · · · · · · · · · · · · ·	
Dimension:	130*128*242mm.
Net Weight	1.10kg.
External Interface:	USB, photoelectric interface, can directly insert a USB disk to
	Upload information.
Voltage:	DC16.8v lithium battery, print continuously more than 10
	Hours and 20 hours standby.
Control Panel:	touch-screen.
Power Consumption:	The average power consumption is lower than 5W.
Working Environment	: Temperature:0 - 38 degree; humidity: 10% - 80%.
Printing Material:	Board, Carton, Stone, Pipe, Cable, Metal, Plastic product,
	Electronic, Fiber Board, Light Steel Keel, Aluminum Foil.

OUR OTHER MODEL: NT- 1270 NT- 2540 NT- 5080

NIYATECH ENGINEERS



A-20, COMERCIAL COMPLEX GOVINDPURAM GHAZIABAD U.P. - 201013

Mo. +91- 8375877122 , Email:info@niyatechengineers.com

www.niyatechengineers.com